

# BlueEyes BE-4211 Video Server

www.BlueEyes.com.tw

## Feature

- Ž Our comprehensive Plug & Play features:,
  - The PnP IP address- supports UPnP protocol.
  - The PnP configuration- USB interface for setup.
  - The PnP recording- built-in SD card for alarm and schedule recording
- Ž Digitizes video signal and transmits via TCP /IP network.
- Ž Built-in motion detection (96 independent blocks with 5 levels of sensitivities per channel).
- Ž Supports a wide range of PTZ cameras.
- Ž Supports 14 languages user interface, including Traditional Chinese and English.
- Ž Supports 1DI / 1DO .
- Ž USB Interface for setup.



## Specification

Video System	NTSC / PAL	Alarm and event management	I/O : 1 Alarm input, 1 Alarm output Trigger: Advanced MD (96 zones, 5 levels of sensitivity) Action: FTP, E-mail, Save to SD card
Video compression	MJPEG / MPEG-4	Network Interface	Ethernet (RJ-45Wired, 10/100 Base-TX), MDIX Support
Resolutions & Frame rate	D1 / Half D1 / CIF 30(25)/ 24/ 15 / 5 FPS, adjustable	Power Requirement	12V DC / 200Ma
Pan/Tilt/Zoom Support	A wide range of analog PTZ dome camera is supported	Power Consumption	2.5W
MJPEG picture size	4 ~ 64 KB	System Integration Support	HTTP-API / SDK / ActiveX component for software integration RTC Support
MJPEG-4 picture size	64kbps~8Mbps (Bit rate)	Installation, management, and maintenance	Upgradeable through SD Card, USB, and FTP
MJPEG watermark	Digital Signature	Remote Client Software	Web browser or IP-Surveillance
Network Throughout	2.0 Mbit/Sec	Operating environment	0°C ~50°C (32°F ~ 122°F)
Image Settings	Auto White balance: On/Off Contrast, Brightness, Hue, Saturation	Client PC Requirements	Windows OS: 2000/XP Internet Explorer 6.0 or higher
Audio	RCA Audio in/out: 1/1, 8 kHz sampling, u-law	Approvals	FCC, CE, RoHS
Time Stamp	Date / Time / Location	Protocols	TCP/IP, DHCP, HTTP, ICMP, UPnP, ARP, DNS, DDNS, PPPoE, FTP, SMTP
Camera title	15 characters	Dimension (WxHxD) and weight	110(W)x60.5(H)x33.5(D)mm 250g(excluding power adapter )
Security	10 users with 3 levels with authority IP Filtering		
Connector	Analog composite video input / output: 1 / 1, 1Vpp, 75 ohm Serial port: 1 set RS-485 USB port 1.1 device SD card(SHDC Support), recording in JPEG Snapshot / AVI File		

## Ordering Information

Order NO.	Product Type
BE-4211	BE-4211 Video Server